




BLOCK 1, 5 & 6




REAR ELEVATION
SCALE 1:100
ALL LEVELS, DIMENSIONS, DEPTHS OF EXCAVATIONS, HEIGHTS OF PLINTHS, NUMBER OF STEPS AND SIZES OF FOUNDATIONS TO BE DETERMINED ON SITE




SIDE A ELEVATION
SCALE 1:100
ALL LEVELS, DIMENSIONS, DEPTHS OF EXCAVATIONS, HEIGHTS OF PLINTHS, NUMBER OF STEPS AND SIZES OF FOUNDATIONS TO BE DETERMINED ON SITE



SIDE B ELEVATION
SCALE 1:100
ALL LEVELS, DIMENSIONS, DEPTHS OF EXCAVATIONS, HEIGHTS OF PLINTHS, NUMBER OF STEPS AND SIZES OF FOUNDATIONS TO BE DETERMINED ON SITE



ROOF PLAN
SCALE 1:200



FRONT ELEVATION
SCALE 1:100

SURFACE BED NOTE:
30mm SCREED ON 85mm SURFACE BED ON 250micron DPM ON TERMITE TREATED WELL COMPACTED FILL MIN 150mm THICK

BUILDING SEALING:
ROOFS, EXTERNAL WALLS, AND FLOORS THAT FORM THE BUILDING ENVELOPE AND ANY OPENING SUCH AS WINDOWS AND DOORS IN THE EXTERNAL WALLS FABRIC SHALL BE CONSTRUCTED TO MINIMIZE AIR LEAKAGE. THE BUILDING SEALING CAN BE DONE BY METHODS SUCH AS CAULKING, OR ADDING SKIRTING, OR CORNICES.
4.4.3.4.1 A SEAL TO RESTRICT MOISTURE. ALL SHALL BE FITTED TO EACH EDGE OF AN EXTERNAL DOOR AND OTHER SUCH OPENING THAT a.SERVES A CONDITIONED SPACE, OR b.SERVES A HABITABLE ROOM IN CLIMATE ZONES 1,2,4&6
4.4.3.4.1 THE SEAL MAY BE A FOAM OR RUBBER COMPRESSIBLE STRIP OR A FIBROUS SEAL

EXTERNAL FINISHES
♦ ROOF FINISH : CONCRETE TILES
♦ FACE BRICK
♦ UPVC WINDOWS
♦ TILED FLOORS
♦ MINIMUM PLINTH OF 255mm
♦ ALL GLAZED SECTIONS TO BE IN ACCORDANCE WITH THE N-SECTION OF THE NBRI & SABS -0137
♦ SITE TO BE EXCAVATED TO SUIT TWO FLOOR LEVELS TO DWELLING

PLEASE NOTE: All confirmation and / or certificates to be provided on a Company Letterhead of the respective manufacturer / supplier / installer / specialists.
fenestration specialists:
1. SANS 613 Certificate
2. U & SHGC Value Certificates / SAFIERA Certificates.
Roof specialists:
3. Confirmation that roof overhangs are as indicated on drawings.
4. Confirmation that the roof insulation installed has the required R-values as shown on drawings.
Electrical specialists
5. Energy consumption & demand - Confirmation that wattage of lighting installed does not exceed wattage demand as indicated on drawings.
Hot water services specialists
6. Hot water pipes - Confirmation that all hot water pipes are insulated with a minimum R-value of 1.
7. Hot water system - Confirmation of the type of hot water system used.

GENERAL NOTES TO ALL CONTRACTORS
♦ ACCORDING SANS 10400
♦ ALL LEVELS, DIMENSIONS, DEPTHS OF EXCAVATIONS, HEIGHTS OF PLINTHS, NUMBER OF STEPS AND SIZES OF FOUNDATIONS TO BE DETERMINED ON SITE
♦ READ FIGURED DIMENSIONS IN PREFERENCE TO SCALING
♦ DRAWINGS PREPARED ON SURFACE EXAMINATION ONLY
♦ ALL WORK DONE SHOULD COMPLY WITH STANDARD AND LOCAL BUILDING REGULATIONS 0 - 400

NOTES TO PITCH ROOF : A
♦ ACCORDING SANS 10400
♦ ROOF PITCH: 26°
♦ ROOF FINISH: CONCRETE ROOF TILES
♦ BATTENS: 38x38 @ 320 c/c
♦ DAMP/DUST MEMBRANE: " TALCOM " WHITE BY GUNDEL
♦ TRUSSES: GRADE 7 TIMBER AT 700c/c
♦ RAFTER: 152x38 to match existing
♦ TIE-BEAMS: 152x38 to match existing
♦ WALL PLATE: 114x38
♦ BRANDING: 38x38
♦ CEILING: 6mm THICK " RHINOBOARD " WITH 70mm CAVED CORNICE
ALL ROOFS TO ENGINEER AND MANUFACTURE'S DETAIL

NOTES FOR WALLS:
♦ ACCORDING SANS 10400
♦ LINTOLS: PRESTRESSED CONCRETE LINTOLS OVER ALL OPENINGS
♦ ROOF ANCHORS: GALVANISED STRAPS TO BE BUILT INTO WALLS @ - 3 COURSES DEEP
♦ LINTOLS: PRESTRESSED CONCRETE LINTOLS OVER ALL OPENINGS EXCEPT WHERE FACE BRICK OCCURS THEN BRICK ON EDGE WITH BRICKFACE ABOVE - 3 COURSES SHOULD BE USED

WINDOWS NOTES :

♦ ALL GLAZED SECTIONS TO BE IN ACCORDANCE WITH THE SANS 10400

NORMAL THICKNESS OF GLASS	MAXIMUM SIZE OF GLAZING
3mm	0,75m ²
4mm	1,50m ²
5mm	2,10m ²
6mm	3,20m ²

NOTES FOR FLOORS :
♦ ACCORDING SANS 10400
♦ SKIRTING: 70X119 HARDWOOD WITH 19mm QUADRANT
♦ FLOOR FINISH: AS INDICATED ON PLAN
♦ SCREED: MINIMUM 25mm SAND OR CEMENT
♦ SURFACE BED: 85mm CONCRETE CEMENT FLOOR SLAB ON 250 MICRON DAMP PROOF MEMBRANE ON WELL COMPACTED EARTH FILL

DRAINAGE :
♦ ACCORDING SANS 10400
♦ I.E'S TO ALL CONNECTIONS
♦ R.E'S AT ALL CHANGE OF DIRECTION & HEAD OF DRAIN WITH MARKED COVERS AT GROUND LEVEL
♦ DRAIN PIPES EXCEEDING 6,0m TO JUNCTION TO HAVE OWN # 110 OVP
WHERE DRAINAGE OCCURS UNDER FOUNDATIONS AND CONCRETE FLOOR SLAB, DRAINAGE PIPES TO BE PROTECTED AGAINST THE LOAD
♦ MINIMUM INVERT LEVEL OF DRAIN 460mm
♦ # 110 OVP AT HEAD OF DRAIN
♦ WHERE ONE - PIPE SYSTEM OCCUR: SEE NOTES TO ELEVATIONS
♦ MINIMUM FALL OF DRAIN: 1:60
♦ WHERE FALL EXCEEDS 1:10, BACK DROPS TO BE PROVIDED TO ENSURE MAXIMUM FALL ONLY 1:10

MEMBER: ANTONELLA F. R. JUNG
Professional Senior Architectural Technologist
REG. NO. : ST0672
BUSINESS C.C NO: 2001/ 062828 / 23



PROPOSED NEW SHRA DEVELOPMENT ON ERF 486 PRINCESS EXT.60
PROPERTIES ARE NOTARIALLY TIED FOR JIDMAC SOCIAL HOUSING

I hereby approve this drawing (I) for the design contained herein an (II) for submission to the Local Authority for their approval

OWNER'S SIGNATURE / AUTHORISED REPRESENTATIVE DATE
Who warrants his authority to sign

WORKING DRAWING
BLOCK 1,5 & 6: Elevation- rear, side A & Side B, & Roof plan

AREA: BLK 1313,30sqm
DATE: JULY 2024 DWG NO. : THPRINCESS ERF 486- WD
DRAWN BY: AFRJ SHEET NO. : 9/20 REVISION NO. : 3

COPYRIGHT This drawing and the copyright therein belongs to Fineline Architectural Design CC and the drawing may not be reproduced in any form without the written permission of Antonella Jung in accordance with the copy right act of 98/1978